

E130 FOCUS^{AL}

Leading-Edge Technology for Advanced Residential Metering Applications

The FOCUS[®] family of metering products provides the utility industry with an advanced, reliable and economical solid-state meter platform for advanced metering applications. The FOCUS AL utilizes a single circuit board design which allows room for installation of a modular communications board or a KYZ option output board. Fewer parts and connectors throughout the design increase reliability and contribute to better overall endpoint performance. Highly accurate load performance and the use of a field-proven Digital Multiplication Measurement Technique ensure reliability and dependability during the entire life of the FOCUS meter.

Meter reconfiguration can be accomplished optically through the configuration port located on the front cover.

- Select from displayable positive, negative, net and added (security) metrics
- Change the displayed information, order or digits
- Configure a CT/PT meter multiplier to obtain a direct reading
- Preset or reset kWh
- Adjust calibration

With a focus on customer satisfaction, we are committed to providing the best metering solution in terms of capability, technology and affordability. By utilizing our experience and technology with that of our strategic allies and development partners, we provide metering solutions that cover the range of utilities' residential metering needs.



Key Benefits

- Digital Multiplication Measurement Technique
- Non-volatile memory
- Designed for a 20+ year life
- Meets or exceeds industry and ANSI standards
- Uses ANSI protocol (between meter and AMR device)
- 6 digit LCD and 2 Alpha ID
- Selectable meter multiplier up to 240 (1200:5 CT)

Specifications

General Specifications	Active Energy “kWh-only” meter	
	Digital Multiplication Measurement Technique	
	Non-Volatile Memory	
	Designed for 20+ years life	
	Meets ANSI standards for performance	
	Utilizes ANSI protocol (between meter and AMI device)	
	8-Digit LCD	
	Display scroll sequence programmable (factory or end user)	
	Configuration Port – cover does not have to be removed	
Operating Temperature	-40C to +85C under cover	
Nominal Voltage	120V or 240V	
Operating Voltage	80% to 115% of Vn	
Frequency	60Hz +/- 5%	
Humidity	5% to 95% relative humidity, non condensing	
Starting Load (Watts)	Class 20	0.005 Amp (0.6W)
	Class 100	0.030 Amp (3.6W)
	Class 200	0.050 Amp (12W)
	Class 320	0.080 Amp (19.2W)
	Class 480	0.120 Amp (28.8W)
Voltage Burden	≤ 1.8W Max	
Load Performance Accuracy	Accuracy Class 0.5% – typical accuracy 0.2%	
Available Forms	Self-Contained	1S, 2S, 2SE, 12S, 25S
	Transformer Rated	3S, 4S
	K-Base	2K
Display Options	Energy Metrics: +kWh, -kWh, Net kWh, and added kWh (Security)	
	Metric Energy Display Format – 4x1, 4x10, 5x1, 5x10, 6x1 or 6x10	
AMI Platform	Modular or Integrated	
Selectable Meter Multiplier	Up to 240 as result of PT ratio • CT ratio	
Applicable Standards	ANSI C12.1 for electric meters	
	ANSI C12.10 for physical aspects of watt hour meters	
	ANSI C12.19 Utility Industry End Device Data Tables	
	ANSI C12.20 for electricity meters, 0.2 and 0.5 accuracy classes	
	CAN3-C17-M84 Canadian specifications for approval of type of electricity meters	

2800 Duncan Road
Lafayette, IN 47904 U.S.A
Phone: **765.742.1001** • Tech Support: **800.777.2774**
FAX: **765.429.0936**
www.landisgyr.com

Landis+
Gyr+
manage energy better